



## Graffiti Eater Masonry

### DESCRIPTION

Graffiti Eater Masonry is a user friendly blend of organic solvents designed to remove graffiti from masonry building surfaces. Graffiti Eater Masonry has been specially blended using a wide range of solvents, to produce a product capable of removing graffiti caused by all types of enamel paint, leather dyes and acrylic paints. Graffiti Eater Masonry may remove underlying paint where graffiti is on a pre-painted surface. Graffiti Eater Masonry also contains special fragrances to ensure minimum disruption to customers and the general public.

### APPLICATION

The method of application depends on the type of surface, size and nature of the graffiti and how long the graffiti has been 'in situ', eg. graffiti which has been on the surface for some time will be harder to remove than graffiti that has not fully cured, or has not been baked by the sun. Ideally, removal should occur within 24 hours.

**For areas under 10 square meters** - apply Graffiti Eater Masonry by applicator brush and leave in contact with the graffiti for at least 5 minutes. Apply more Graffiti Eater Masonry by applicator brush and use a circular scrubbing motion to remove graffiti. As the graffiti breaks down it is essential that Graffiti Eater Neutraliser is used to wash off the residue immediately. For heavily coated areas or areas that have been subjected to baking by the sun, the above process may need to be repeated. Graffiti Eater Masonry may not be totally effective on all graffiti as experimentation by graffitiists produces new 'cocktails' continually. In these cases it is recommended that a Graffiti Eater representative be contacted.

**For areas over 10 square meters** - it may be cost effective to utilise high pressure water equipment for larger areas. Apply Graffiti Eater Masonry as for smaller areas. Leave in contact with the graffiti for at least five minutes before applying a second coating using a stiff bristle brush to assist in removal. As the graffiti breaks down, use the high pressure water, to hose off the residue. Repeat the process if necessary.

We recommend regular removal process be undertaken rather than allowing the graffiti to build up as the removal process will then be harder and more costly in labour and materials. Graffiti Eater representatives are available to provide assistance during removal process.

### OH&S

Ensure adequate ventilation during use. Wear Type A full face organic vapour respirator in confined areas. (Ref. Australian Standard 1715 - 1991). Avoid contact with skin and eyes, wear eye protection, Vitron or PVA gloves and solvent resistant overalls during use.

### IMPORTANT NOTICE TO CUSTOMERS

Since the use of this product is beyond the control of either seller or manufacturer, their only obligation shall be to replace any quantity of product which is proven defective. They cannot assume any risk or liability in excess of the purchase price of the product itself, which does not include labour or any consequential damages from the use of this product. Determining the suitability of this product for any intended use shall be solely the responsibility of the user. **ALWAYS TEST FIRST.**